



Block-outs with black reverse side - opaque, ideal for trade fair and shop fitting

Thanks to the black reverse side, which prevents light from shining through, our fabrics ensure optimum presentation of your motifs both indoors and outdoors. **Our block-out materials stand for outstanding results and quality:**

- opaque and light-proof reverse side, prevents light from shining through
- high degree of whiteness of the textile for the best colour reproduction in printing
- optimum running behaviour in the printer in sublimation as well as in UV and latex machines
- very good crease recovery and crease-free clamping
- many stock widths for optimum utilisation
- available for seamless large-format motifs up to a width of 505 cm
- flame-retardant and tested according to EN 13501 standard

Overview of our block-outs		
Midnight Pro 7034BBFS	 our BESTSELLER - with a soft feel and textile surface, perfect for use in frame systems suitable for sublimation printing (transfer and direct), UV and latex printing the best option for printing with UV inks stock widths: 260 cm, 320 cm, 410 cm, 505 cm weight: 270 g/m² 	
Midnight Soft 7186RBBFS	 block-out with textile structure and soft feel suitable for sublimation printing (transfer and direct), UV and Latex printing Stock widths: 260 cm, 320 cm, 410 cm, 505 cm weight: 270 g/m² 	
BlackBack 7255KMGFS	 perfect elasticity in length and width for easy processing suitable for sublimation printing (transfer and direct) and latex printing stock widths: 260 cm, 320 cm weight: 260 g/m² 	
BlackSilk GFS 7019KMGFS	 special block-out with a very fine, slightly shiny surface suitable for sublimation printing (transfer and direct), UV and latex printing stock widths: 320 cm weight: 240 g/m² 	





Instructions for printing with sublimation inks and fixing the product in the calender:

- guideline: approx. 185 °C fusing temperature with approx. 40 50 s fusing time
- if the temperature is too high and the fusing time too long, the material may stick to the protective paper
- goods can also be fixed without protective paper, this has to be checked separately

Washability of the textiles / durability of the black reverse side:

Washing the material is not recommended, mechanical action may cause the fabric to shrink. The adhesion of the ink should also be checked.

To ensure the longevity of the black block-out layer, we recommend avoiding pointed or sharp objects and not dragging them across the surface. This will keep the coating in perfect condition and ensure optimum results.

When using solvent-based adhesives, it is advisable to carry out a test for interactions with the coating in advance.

Which block-out fits to your application?

Do not hesitate to contact us! We will be happy to send you samples so that you make the perfect choice.





...there is also a white block-out for trade fair and shop fitting:

Be inspired and find out more in our product video:



